# Runxin Automatic Softener Valve

## 63520(F95A1) / 63620(F95A3)

20m³/h

Automatic Softener Valve:63620(F95A3)

Runxin Automatic Softener Valve F95A1

## Technical Parameters:

●Water Pressure----------0.2—0.6MPa

●Water Temperature----------5℃-50℃

●Transformer Output----------DC24V、1.5A

●Water Turbidity---------- < 5FTU

●Inlet/Outlet----------2″ Male

●Drain----------1.5″ Male

●Brine Line Connector----------3/4″ Male

●Base----------4″-8UN

●Riser Pipe----------1.5 ″D-GB

●Max Flow Rate----------20 m3/h

●Suitable Tank Size (in)---------- 28″ ~ 40″

## Product Characteristics:

■It adopts hermetic head faces with high degree pottery and corrosion resistance for opening and closing.

■No water pass the valve of single tank type in regeneration

■Brine refill controlled by electronic ball valve

■LED dynamic screen display LED.The stripe on dynamic screen flash, it indicates the control valve is in service, otherwise, it is inregeneration cycle.

■Having long outage indicator

■It can choose time clock type or meter type by program selection

■Buttons are locked when no operation within 1 minute

■Having interlock function

■With signal output connector

■With remote handling input connector

■With pressure relief connector

■All parameters can be modified according to the need

## Range of Application:

(Down-flow Regeneration) be suitable for the Ion exchange equipment that treat water hardness ≤6.5mmol/L

Boiler softening water system

RO pretreatment softening system, etc